



**SAFETY DATA SHEET**  
**COLOUR MATCH AEROSOL PAINT**

**1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING**

PRODUCT NAME COLOUR MATCH AEROSOL PAINT

PRODUCT NO. YAB128, YAV110, YAF107, YNC018, YNC019, YAB148, YAF066, YAV124, YNC020, YAF078, YAB096, YAV074, YAF030, YAB121, YAB023, YNC021, YNC022, YAF176, YAB169, YAB021, YAF128, YAF135, YAF156, YAF088, YAB033, YAF167, YAV107, YNC011, YNC012, YAF147, YAF184, YAV084, YAB180, YAB150, YAV087, YAF127, YAB001, YAD039, YAD022, YAB167, YAB101, YAW038, YAF136, YAV076, YAB062, YNC001, YAR054, YAF085, YAF158, YAF011, YAD028, YTA001, YNC013, YAV101, YAF048, YAB119, YAV091, YAW025, YAB143, YAF108, YAF077, YAB097, YAB070, YNC014, YAF081, YAF073, YNC025, YAF182, YAR087, YAB193, YAV094, YAF132, YAF151, YAB164, YAV089, YAB186, YAV102, YAF144, YNC002, YAB174, YAO003, YAB165, YNC026, YAW046, YAB134, YAV058, YAB141, YNC027, YAV106, YAB138, YAB181, YNC028, YAW028, YAF089, YAF038, YAD020, YAD029, YAF170, YAF164, YAV072, YAF146, YMW003, YAB060, YAY021, YAV088, YAX018, YAD036, YAR097, YAD027, YMW001, YAW026, YAB177, YAF120, YAF064, YAC002, YAL005, YNC029, YAB158, YAR077, YAD023, YAB157, YAB099, YAB100, YAF180, YTA005, YAV022, YAV054, YAB145, YAB007, YAF148, YAB055, YAB123, YAR090, YNC015, YAB191, YNC016, YAF086, YAF059, YAB127, YGB014, YSB014, YMB014, YGW014, YPA014, WPF012, YAF166, WPF014, WPF015, WPF017, WPF018, WPF020, WPF021, YAF074, YAB131, YAV105, YAF139, YAB166, YAV090, YAF117, YAB149, YAB179, YAF177, YAB192, YAD009, YAV118, YAF169, YAF079, YAB162, YAF137, YAB173, YAD038, YNC003, YAF067, YAF163, YAF093, YAR030, YAF162, YAF058, YAB098, YAF140, YMW002, YAD018, YAF149, YAF150, YAB163, YAV075, YAV085, YAB168, YAF175, YAF095, YAR063, YAD033, YAB182, YAB091, YAV061, YNC004, YNC005, YAF159, YNC006, YAV120, YNC007, YAV121, YAF183, YAB196, YAF072, YAV116, YNC008, YNC009, YNC010, YAF155, YAF083, YAB095, YAB135, YNC024, YAF119, YAB172, YAB137, YAD037, YAF160, YAF040, YAD015, YAF076, YAF172, YAF103, YAF179, YAV064, YAF115, YAF153, YAB140, YAV069, YAF154, YNC017, YAF068, YAB125, YAF082

INTERNAL ID D

APPLICATION Paint

SUPPLIER TETROSYL LIMITED  
 BEVIS GREEN WORKS  
 WALMERSLEY  
 BURY  
 BL9 6RE  
 0161 764 5981  
 0161 797 5899  
 info@tetrosyl.com

**2 COMPOSITION/INFORMATION ON INGREDIENTS**

| Name                  | EC No.    | CAS-No.    | Content | Classification                                  |
|-----------------------|-----------|------------|---------|---|
| PETROLEUM DISTILLATES | 265-185-4 | 64742-82-1 | < 1%    | Xn;R65. N;R51/53. R10,R66.                      |
| SHAP 70               | 270-704-2 | 68476-85-7 | 10-30%  | F+;R12.   |
| TOLUENE               | 203-625-9 | 108-88-3   | 60-100% | F;R11 Repr. Cat. 3;R63 Xn;R48/20,R65 Xi;R38 R67 |

The Full Text for all R-Phrases are Displayed in Section 16

**COMPOSITION COMMENTS**

The Data Shown is in accordance with the latest EC Directives.

**3 HAZARDS IDENTIFICATION**

Extremely flammable. Vapours may cause drowsiness and dizziness. Irritating to skin. Possible risk of harm to the unborn child. Harmful: danger of serious damage to health by prolonged exposure through inhalation.

CLASSIFICATION Xn;R48/20. Rep 3;R63. Xi;R38. F+;R12. R67.

**HUMAN HEALTH**

Contains a substance/a group of substances which may impair fertility. Contains a substance/a group of substances which may cause harm to the unborn child. Contains a substance/a group of substances which may cause harm to breastfed babies. See section 11 for additional information on health hazards.

## COLOUR MATCH AEROSOL PAINT

### 4 FIRST-AID MEASURES

#### GENERAL INFORMATION

Remove affected person from source of contamination. Get medical attention immediately!

#### INHALATION

Move injured person into fresh air immediately. Call an ambulance. Be aware that symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure. Take along these instructions. Place unconscious person on the side in the recovery position and ensure breathing

#### INGESTION

Immediately rinse mouth and drink plenty of water or milk. Keep person under observation. Do not induce vomiting. If vomiting occurs, keep head low. Transport immediately to hospital and take these instructions.

#### SKIN CONTACT

Remove contaminated clothing immediately and wash skin with soap and water. Consult a physician for specific advice. Burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

#### EYE CONTACT

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Immediately transport to hospital or eye specialist.

### 5 FIRE-FIGHTING MEASURES

#### EXTINGUISHING MEDIA

Use fire-extinguishing media appropriate for surrounding materials.

#### SPECIAL FIRE FIGHTING PROCEDURES

Beware, risk of formation of toxic and corrosive gases.

#### SPECIFIC HAZARDS

In case of fire, toxic and corrosive gases may be formed.

#### PROTECTIVE MEASURES IN FIRE

Leave danger zone immediately.

### 6 ACCIDENTAL RELEASE MEASURES

#### PERSONAL PRECAUTIONS

Wear protective clothing as described in Section 8 of this safety data sheet. In case of spills, beware of slippery floors and surfaces.

#### ENVIRONMENTAL PRECAUTIONS

The product should not be dumped in nature but collected and delivered according to agreement with the local authorities.

#### SPILL CLEAN UP METHODS

For waste disposal, see section 13. When dealing with a spillage, please consult the section relating to suitable protective measures. Provide ventilation and confine spill. Do not allow runoff to sewer. Absorb spillage with non-combustible, absorbent material.

### 7 HANDLING AND STORAGE

#### USAGE PRECAUTIONS

Read and follow manufacturer's recommendations. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not eat, drink or smoke when using the product. Wear full protective clothing for prolonged exposure and/or high concentrations. Eye wash facilities and emergency shower must be available when handling this product. Pregnant or breastfeeding women must not handle this product.

#### STORAGE PRECAUTIONS

Keep away from heat, sparks and open flame. Store in tightly closed original container in a cool, dry well-ventilated place.

#### STORAGE CLASS

Flammable liquid storage.

### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

| Name                  | Std | LT - ppm   | LT - mg/m3    | ST - ppm    | ST - mg/m3    |
|-----------------------|-----|------------|---------------|-------------|---------------|
| TOLUENE               | WEL | 50 ppm(Sk) | 191 mg/m3(Sk) | 150 ppm(Sk) | 574 mg/m3(Sk) |
| PETROLEUM DISTILLATES | WEL |            | 600 mg/m3     |             |               |
| SHAP 70               | WEL | 1000 ppm   | 1750 mg/m3    | 1250 ppm    | 2180 mg/m3    |

## COLOUR MATCH AEROSOL PAINT

### PROTECTIVE EQUIPMENT



### PROCESS CONDITIONS

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station.

### ENGINEERING MEASURES

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined workplace exposure limit is not exceeded.

### RESPIRATORY EQUIPMENT

Wear suitable respiratory protection. Check that mask fits tight and change filter regularly.

### HAND PROTECTION

The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Protection against this substance requires special consideration. Protective gloves and goggles must be used if there is a risk of direct contact or splash.

### EYE PROTECTION

Wear full-face visor or shield.

### OTHER PROTECTION

Provide eyewash station. AVOID ALL SKIN AND RESPIRATORY CONTACT!

### HYGIENE MEASURES

Wash contaminated clothing before reuse. Wash at the end of each work shift and before eating, smoking and using the toilet. Provide shower facilities near the work place.

### SKIN PROTECTION

Protection suit must be worn.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

COLOUR Misc. colours

## 10 STABILITY AND REACTIVITY

### STABILITY

No particular stability concerns.

## 11 TOXICOLOGICAL INFORMATION

### TOXICOLOGICAL INFORMATION

This material is very toxic.

### GENERAL INFORMATION

Known or suspected carcinogen for humans. Possible reproductive impact.

### HEALTH WARNINGS

This chemical may cause skin/eye irritation and burns (corrosive). May cause severe internal injury. May cause unconsciousness, blindness and possibly death.

#### Other Health Effects

Carcinogen Category 3.

### ROUTE OF ENTRY

Inhalation. Ingestion. Skin and/or eye contact. Skin absorption.

### SPECIFIC EFFECTS

Contains a substance/a group of substances which may cause harm to breastfed babies. Contains a substance/a group of substances which may cause cancer by inhalation. Contains a substance/a group of substances with possible risk of harm to the unborn child and with possible risk of impaired fertility.

## 12 ECOLOGICAL INFORMATION

### ECOTOXICITY

Dangerous for the environment if discharged into watercourses.

## COLOUR MATCH AEROSOL PAINT

### 13 DISPOSAL CONSIDERATIONS

#### GENERAL INFORMATION

When handling waste, consideration should be made to the safety precautions applying to handling of the product. Only experts should be permitted to carry out disposal of this material.

#### DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Absorb spillage with non-combustible, absorbent material.

### 14 TRANSPORT INFORMATION

#### GENERAL

Full protective clothing should be worn when handling this product.



|                      |          |                  |                |
|----------------------|----------|------------------|----------------|
| UK ROAD CLASS        | 2.1      |                  |                |
| PROPER SHIPPING NAME | AEROSOLS |                  |                |
| UN NO. ROAD          | 1950     | UK ROAD PACK GR. | #              |
| ADR CLASS NO.        | 2.1      | ADR CLASS        | Class 2: Gases |
| ADR PACK GROUP       | #        | ADR LABEL NO.    | 2.1            |
| CEFIC TEC(R) NO.     | 20G5F    | RID CLASS NO.    | 2.1            |
| RID PACK GROUP       | #        | UN NO. SEA       | 1950           |
| IMDG CLASS           | 2.1      | IMDG PACK GR.    | #              |
| EMS                  | F-D, S-U | MFAG             | See Guide      |
| MARINE POLLUTANT     | No.      | UN NO. AIR       | 1950           |
| AIR CLASS            | 2.1      | AIR PACK GR.     | #              |

### 15 REGULATORY INFORMATION

#### LABELLING



Harmful



Extremely Flammable

#### CONTAINS

TOLUENE

#### RISK PHRASES

|        |   |
|--------|---|
| R12    | Extremely flammable.  |
| R38    | Irritating to skin.   |
| R48/20 | Harmful: danger of serious damage to health by prolonged exposure through inhalation. |
| R63    | Possible risk of harm to the unborn child.  |
| R67    | Vapours may cause drowsiness and dizziness.   |

#### SAFETY PHRASES

|        |   |
|--------|---|
| S2     | Keep out of the reach of children                     |
| S9     | Keep container in a well-ventilated place.            |
| S13    | Keep away from food, drink and animal feeding stuffs. |
| S16    | Keep away from sources of ignition - No smoking.      |
| S23    | Do not breathe vapour/spray.                          |
| S24    | Avoid contact with skin.                              |
| S36/37 | Wear suitable protective clothing and gloves.         |

### COLOUR MATCH AEROSOL PAINT

- S51 Use only in well-ventilated areas.
- S56 Dispose of this material and its container to hazardous or special waste collection point.

#### DETERGENT LABELLING

- 15-30% Aliphatic hydrocarbons

#### UK REGULATORY REFERENCES

The Control of Substances Hazardous to Health Regulations 1988. Chemicals (Hazard Information & Packaging) Regulations.

#### EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EEC. System of specific information relating to Dangerous Preparations. 2001/58/EEC.

### 16 OTHER INFORMATION

#### GENERAL INFORMATION

Only trained personnel should use this material.

#### ISSUED BY

HS&E Manager.

REVISION DATE 17/05/2006

REV. NO./REPL. SDS GENERATED 5

#### RISK PHRASES IN FULL

- R10 Flammable.
- R11 Highly flammable.
- R12 Extremely flammable.
- R38 Irritating to skin.
- R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R63 Possible risk of harm to the unborn child.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

#### DISCLAIMER

The information provided in this document has been compiled on the basis of our current knowledge and is believed to be in accordance with the requirements of the Dangerous Substances Directive, Dangerous Preparations Directive and Safety Data Sheets Directive. The information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any particular conditions or process. The conditions and extent of storage and use of material are outside of our control and within the control of the possessor or user. Consequently it is the responsibility of the possessor or user to satisfy themselves as to the completeness of such information and the suitability of the material for their own particular circumstances, conditions or use.